Professional manufacturer of high power industrial LED grow light for marijuana

KINGROWLIGH

The foldable series is a high-performance toplighting solution for commercial horticulture cultivation and indoor planting.



Product description

Foldable LED Grow Light Plus is equipped with 10 100W light bars for a total power of 1000W, with a high level of PPF output of 2800 µmol/s and photon potency of 2.8 µmol/J. The fixture uses top-diode Samsung LM281B+ and LEDSTAR chips with enhanced 460nm blue light and increased 730nm IR to meet the PPFD growing needs of plants at all times. 4ft x 6ft can cover a larger area, combined with a unique light distribution angle for even PPFD distribution. 0-10V dimmable application control can be used to easily control the output.

Foldable LED Grow Light Plus

Rev1.0[2023/06/27]

KINGROWLIGHT Foldable LED Grow Light Plus

Professional manufacturer of high power industrial LED grow light for marijuana

Specifications

| Model | G1000V1P06 Plus | | |
|---|-------------------------|--|--|
| Input voltage | 100-277VAC, 50/60Hz | | |
| Nominal wattage | 1000W(±5%) | | |
| Typical PPF | 2800µmol/s | | |
| Efficacy | 2.8µmol/J | | |
| Spectrum | FSP | | |
| Dimming | 0-10V | | |
| IP rating | IP54(indoor using) | | |
| Mounting height | ≥6" above canopy | | |
| Structure material | Al6063 | | |
| Cooling | Passive | | |
| Lifetime | ≥50,000hrs | | |
| Ambient operating temperature -20°C~+40°C | | | |
| Certifications | ETL,CE | | |
| Warranty | 5 years | | |
| Product size | 66.9″L x 42.7″W x 2.5″H | | |
| Product weight | 35.9lb | | |
| Package size | 44.9″L x 5.1″W x 38.8″H | | |
| Package weight | 40.1lb | | |
| | | | |


Nominal electrical AC input

| AC voltage | 120V | 208V | 240V | 277V |
|---------------|--------|-------|-------|-------|
| Input current | 8.576A | 4.75A | 4.11A | 3.53A |
| Input power | 1028W | 989W | 986W | 979W |
| Power factor | 0.997 | 0.985 | 0.978 | 0.974 |

Main features

- Foldable fixture easy breeze to ship, store, and install, save costs
- 1000W high light intensity for higher yield
- Full spectrum with 730nm IR and enhanced 460nm blue light
- SAMSUNG LM281 diodes and SOSEN drivers
- Compatible with UL1598/UL8800/DLC
- Knob 0-10v dimming and RJ12 integrated control
- Built-in power supply, equipped with 3m cable plug, plug and play

Full spectrum



Dimensions





Rev1.0[2023/06/27]

Specifications and dimensions subject to change without notice, contact Kingrowlight for questions and the most current information.